

US TYPE High Tensile Forged Shackle G209



Feature of US TYPE High Tensile Forged Shackle
G209
US type
Material: 45#
Forged Steel
Ultimate load: W.L.L*4
Surface Treatment: Self-color, Zinc pleated, Hot dip
dalvanized,
Trivalent chromium plating zinc, powder coating

US TYPE High Tensile Forged Shackle G209 Feature

US type
Material: 45#
Forged Steel
Ultimate load: W.L.L*4
Surface Treatment: Self-color, Zinc pleated, Hot dip dalvanized,
Trivalent chromium plating zinc, powder coating

US TYPE High Tensile Forged Shackle G209 Specification

Nominal Size	Working load limit(tons)	Dimensinons(mm)											Weight each
		A	B	C	D	E	F	G	H	I	M	N	
3/16	1/3	9.656	3.522	4.4	8.515	2.14	2.24	9.37	3.4	0.628	4.4	8.50	0.03
1/4	1/2	11.97	8.528	7.6	3.519	8.15	5.32	5.46	7.4	8.535	1.6	3.50	0.05
5/16	3/4	135	9.653	1	7.852	1.319	1.37	3.53	5.6	42.27	8.50	0.09	
3/8	1	16.81	1.236	6.9	6.526	2.23	1.45	2.63	6.35	51.59	6.50	0.14	
7/16	1-1/2	19.11	2.742	9.11	2.29	5.26	9.51	5.74	7.85	60.51	1.20	0.17	
1/2	2	20.61	6	47.81	2.733	3.330	2.58	5.83	5.9	6.568	5.12	0.33	
5/8	3-1/4	26.91	9.160	5.16	42.93	8.174	5.106	11.285	17.50	6.2			
3/4	4-3/4	31.82	2.471	5.19	1.51	46	89	126	12.7	101	20.61	0.07	
7/8	6-1/2	36.62	5.484	22.45	8	53	102	148	12.7	114	24.61	0.64	
1	8-1/2	42.92	8.795	5.25	4.68	5.60	5.119	167	14.2	129	26.92	0.28	
1-1/8	9-1/2	46	31.81	0.8	29.574	68.51	31	190	16	142	31.83	0.36	

1-1/4	12	51.535.1119	32.892.576	146 210	17.5156	35.14.31
1-3/8	13-1/2	57	38.1133	36.192	84	162 233 19.1174 38.16.14
1-1/2	17	60.541.4146	39.198.592	175 254	20.6187	41.17.8
1-3/4	25	73	51	178 46.7127	106 225 313	25.4231 57 12.6
2	35	82.557	197 53	146 122 253 348	31	263 61 20.4
2-1/2	55	105 70	267 69	184 145 327 453	35.1330	79.598.9

