

US TYPE High Tensile Forged Shackle G2150



Feature of US TYPE High Tensile Forged Shackle
G2150
US type
Material: 40cr
Forged Steel
Ultimate load: W.L.L*4
Surface Treatment: Self-color, Zinc pleated, Hot dip
dalvanized,
Trivalent chromium plating zinc, powder coating

US TYPE High Tensile Forged Shackle G2150 Feature

US type
Material: 40cr
Forged Steel
Ultimate load: W.L.L*4
Surface Treatment: Self-color, Zinc pleated, Hot dip dalvanized,
Trivalent chromium plating zinc, powder coating

US TYPE High Tensile Forged Shackle G2150 Specification

Nominal Size	Working load limit(tons)	Dimensinons(mm)										Weight each
		A	B	C	D	E	F	G	H	I		
1/4	1/2	11.97	8.56	3.51	5.19	14.04	24.63	9.66	3.50	0.06		
5/16	3/4	13.59	6.57	8.51	9.12	5.44	8.52	9.54	6.27	8.50	1	
3/8	1	16.81	11.29	6.52	3.13	1	58.53	5.85	5	9.65	0.15	
7/16	1-1/2	19.11	2.71	11.22	6.93	6.16	7.54	1.46	3.51	1.20	0.22	
1/2	2	20.61	6	12.73	0.24	1.47	7	46	71	12.70	0.34	
5/8	3-1/4	26.91	9.11	6	38.15	1	95.55	8.58	9.51	7.50	0.67	
3/4	4-3/4	31.82	2.41	9.14	6	60.51	15	70	103	20.61	1.14	
7/8	6-1/2	36.62	5.42	2.45	3	71.51	35	81	120	24.61	1.74	
1	8-1/2	42.92	8.72	5.46	0.58	1	151	93.51	35	25.42	0.52	
1-1/8	9-1/2	46	31.82	8.76	8.59	1	172	103	150	31.83	1.45	
1-1/4	12	51.53	5.13	1.87	6	100	191	115	165	35.14	1.9	

1-3/8	13-1/2
1-1/2	17
1-3/4	25
2	35
2-1/2	55
3	85

57	38.135.184	111	210	127	183	38.16.24
60.541.438.192	122	230	137	196	41.18.39	
73	51	44.5106	146	279	162	230 54 14.2
82.557	51	122	172	312	184	264 51 21.2
105	70	66.5145	203	377	238	344 66.538.6
127	82.576	165	216	429	279	419 89 56

